accuc@ld

ACR45LCALSTO



31.5" x 19.5" x 24.75" (H x W x D)

Pharmacy Series ADA compliant 20" wide built-in undercounter all-refrigerator for vaccine storage, frost-free with a step-to-open door pedal, internal fan, external digital controls and NIST calibrated thermometer, and lock

Highlights:

Less than 32" high to allow installation under lower ADA compliant counters

Specially designed to meet current CDC/VFC vaccine refrigeration guidelines for convenient storage in pharmacies and other healthcare facilities

High temperature alarm includes NIST calibrated external temperature readout (NIST certificate included)

Product Features:

Vaccine refrigerator	Purpose-built to meet the recommendations of the CDC and VFC for reliable vaccine storage
ADA compliant	Sized just under 32" high to allow installation under lower ADA compliant counters
Built-in capable	Front-breathing system allows the unit to be installed under cabinets with minimum clearance
Slim 20" width	Full 2.65 cu.ft. capacity inside conveniently slim footprint
Step-to-open door pedal	Helps lessen germ spread by providing a more sanitary method of opening appliance doors, while allowing efficient access to the unit's interior for added convenience
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
NIST calibrated external temperature display	Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button
Certificate of calibration included	Calibrated to NIST standards in our ISO/IEC 17025:2017 accredited laboratory, with a certificate included for your records
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience





accuc@ld

ACR45LCALSTO Specifications:

Overview			
Nominal Width	20.0" (51 cm)		
Nominal Depth	25.0" (64 cm)		
Nominal Height	32.0" (81 cm)		
Height of Cabinet	31.5" (80 cm)		
Width	19.5" (50 cm)		
Depth	24.75" (63 cm)		
Depth with Handle	23.63" (60 cm)		
Depth with door at 90°	41.0" (104 cm)		
Capacity	2.65 cu.ft. (75 L)		
Defrost Type	Frost-Free		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Amps	1.0		
Voltage/Frequency	115 V AC/60 Hz		
Weight	79.0 lbs. (36 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101076119		
Refrigerator Features			
Door Swing	RHD		
Reversible	Factory Reversible		
Shelf Type			
Chon Type	Wire		
Shelf Qty	Wire 3		
	-		
Shelf Qty	3		
Shelf Qty Adjustable Shelves	3 Yes		
Shelf Qty Adjustable Shelves Thermostat Type	Yes Digital Interior and		
Shelf Qty Adjustable Shelves Thermostat Type Fan Type	Yes Digital Interior and Exterior		
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type	Yes Digital Interior and Exterior R600a		
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	Yes Digital Interior and Exterior R600a 0.99oz.		
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI	3 Yes Digital Interior and Exterior R600a 0.990z. 270.0		
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	3 Yes Digital Interior and Exterior R600a 0.99oz. 270.0 105.0		
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty	3 Yes Digital Interior and Exterior R600a 0.990z. 270.0 105.0		
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty Interior Light	3 Yes Digital Interior and Exterior R600a 0.99oz. 270.0 105.0 4 Yes		

Interior Width	15.0" (38 cm)
Interior Depth	16.13" (41 cm)
Compressor Step Height	3.5" (9 cm)
Compressor Step Width	15.0" (38 cm)
Compressor Step Depth	4.75" (12 cm)

