## accuc@ld

# **ARG18PV**



78.5" x 27.5" x 26" (H x W x D)

Performance series Pharma-Vac 18 cu.ft. upright glass door all-refrigerator for vaccine storage, with antimicrobial silver-ion handle, and hospital grade cord with 'green dot' plug

### **Highlights:**

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

#### **Product Features:**

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines	
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	
Commercial design	Meets UL-471 commercial standards	
Access port	Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment	

## accuc@ld

### **ARG18PV Specifications:**

Overview			
Height of Cabinet	78.5" (199 cm)		
Width	27.5" (70 cm)		
Width with Door Open	28.0" (71 cm)		
Depth	26.0" (66 cm)		
Depth with Handle	27.75" (70 cm)		
Depth with door at 90°	52.0" (132 cm)		
Capacity	18.0 cu.ft. (510 L)		
Defrost Type	Automatic		
Door	Glass		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Amps	1.5		
Voltage/Frequency	115 V AC/60 Hz		
Weight	275.0 lbs. (125 kg)		
Parts & Labor Warranty	2 Years		
Compressor Warranty	5 Years		
UPC	761101084190		
Refrigerator Features			
Door Swing	RHD		
Reversible	Yes		
Shelf Type	Wire		
Shelf Qty	7		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Fan Type	Interior		
Refrigerant Type	R290		
Refrigerant Amount	1.75oz.		
High Side PSI	280.0		
Low Side PSI	90.0		
Wheel Qty	4		
Wheel Qty	4		
Wheel Qty Interior Light	4 Yes		
Wheel Qty Interior Light Temperature Range	4 Yes		
Wheel Qty Interior Light Temperature Range Dimensions	4 Yes 2 to 8°C		

Compressor Step Height	6.5" (17 cm)
Compressor Step Width	24.13" (61 cm)
Compressor Step Depth	6.5" (17 cm)



